[2017 New Exam 400-101 PDF Free Instant Download From Lead2pass (281-300)

2017 August Cisco Official New Released 400-101 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! In recent years, many people choose to take Cisco 400-101 certification exam which can make you get the Cisco certificate and that is the passport to get a better job and get promotions. How to prepare for Cisco 400-101 exam and get the certificate? Please refer to Cisco 400-101 exam questions and answers on Lead2pass. Following questions and answers are all new published by Cisco Official Exam Center: https://www.lead2pass.com/400-101.html QUESTION 281Which two statements about static routing are ture?(Choose two) A. It is highly scalable as networks growB. It reduces configuration errorsC. It can be implemented more quickly that dynamic routingD. It provides better security than dynamic routingE. It requires less bandwidth and fewer CPU cycles than dynamic routing protocols Answer: DE QUESTION 282Which value does VPLS use to make forwarding decisions? A. destination IP address of the packetB. destination MAC of the Ethernet frameC. source IP address of the packetD. source MAC of the Ethernet frame Answer: B QUESTION 283Which three configuration settings must match for switches to be in the same MST region?(Choose three) A. passwordB. region nameC. VLAN-to-instance assignmentD. revision numberE. VLAN namesF. domain name Answer: BCD QUESTION 284Refer to the exhibit. If R4 is configured as shown, which EIGRP routes are present in the R1 routing table? A. 4.4.4.4/32 and 10.2.4.0/24 onlyB. 4.4.4.4/32 and 10.1.4.0/24 onlyC. 4.4.4.4/32,10.2.4.0/24,and 2.2.2.2/32D. 0.0.0.0/0,4.4.4.4/32,and 10.2.4.0/24E. 0.0.0.0/0 and 4.4.4.4/32 only Answer: A QUESTION 285Which two statements about IPv6 multicast address are true? (Choose two) A. An IPv6 host must join the solicited-node multicast group for Solicited-node multicast addresses are based on the lower-order 24 bits of the unicast or anycast addressD. They perform neighbor unreachability detection only for neighbors that send multicast packetsE. Neighbors respone to solicitation messages by sending Router Advertisement messageF. They use UDP packets to perform neighbor unreachability detection Answer: AC QUESTION 286Which type of access list allows granular session filtering for upper-level protocols? A. reflexive access listsB. context-based access listsC. content-based access listsD. extended access lists Answer: A QUESTION 287In which scenario can asymmetric routing occur? A. redundant routers running VRRPB. active/standby firewall setupC. active/active firewall setupD. single path in and out of the network Answer: C QUESTION 288Refer to the exhibit. What is indicated by the show ip cef command for an address? A. CEF cannot switch packet for this route and drops itB. CEF is unable to get routing information for this routeC. CEF cannot switch packet for this route and passes it to the next best switching methodD. A valid entry and is punted to hardware-based forwarding Answer: C QUESTION 289Which two statements about Management Plane Protection are true?(Choose two) A. It supports the SNMP,ssh,TFTP,and HTTP management protocolsB. It supports in-band and out-of-band management interfacesC. It is enabled by default, but it allows all management protocols to pass freely through all interfaces until it is configuredD. It can handle management traffic when IP Cisco Express Forwarding is disabledE. It provides granular control over the management protocols that are allowed on an interfaceF. It works only on out-of-band management interfaces Answer: AC QUESTION 290A network engineer enables OSPF on a Frame Relay WAN connection to various remote sites, but no OSPF adjacencies come up. Which two actions are possible solutions for this issue?(Choose two) A. Change the network type to nonbroadcast multipoint accessB. Configure the neighbor command under OSPF process for each remote siteC. Ensure that the OSPF process number matches among all remote sitesD. Enable virtual linksE. Change the network type to point-to-multipoint under WAN interface Answer: BE QUESTION 291Which two statements about route redistribution default metrics are true?(Choose two) A. When an IGP is redistributed into RIP, it has a default metric of 1B. When an IGP is redistributed into OSPF, it has a default metric of 110C. When an IGP is redistributed into IS-IS, it has a default metric of 115D. When EIGRP is redistributed into OSPF as E2, it has a default metric of 20E. When BGP is redistributed into OSPF, it has a default metric of 1 Answer: DE QUESTION 292Which two GRE features can you configure to prevent fragmentation?(Choose two) A. UDP window sizesB. IP MTUC. PMTUDD. MTU ignoreE. TCP MSSF. DF bit clear Answer: CE QUESTION 293Which three statements about AToM are true?(Choose three) A. The PE routers must share the same VC identifierB. It requires Layer 3 routing between the PE and CE routerC. It requires MPLS between the PE routersD. IP CEF should be disabled on the PE routersE. It supports interworking for Frame Relay, PPP, and Ethernet, but not ATMF. The attachment circuit is configured with the xconnect command Answer: ACF OUESTION 294Refer to the exhibit. You are configuring Router 1 and Router 2 for L2TPv3 tunneling. Which two additional configurations are required to enable Router 1 and Router 2 to establish the tunnel?(Choose two) A. Loopback 0 on Router 1 must be advertised to Router 2B. An IP address must be configured on interface FastEthernet1/0 on Router 1C. Cisco Disconvery Protocol must be enabled on interface FastEthernet1/0 on Router 1D. Router 1 must be configured to encapsulate traffic by using L2TPv3 under the pseudowire-class R1toR2E. Cisco

Express Forwarding must be disabled on Router 1 Answer: AD QUESTION 295Which IPv4 feature can limit indiscriminate flooding of multicast traffic on a VLAN? A. PIM SnoopingB. IGMP SnoopingC. MLD FilteringD. IGMP Filtering Answer: B QUESTION 296Refer to the exhibit. You have configured R1 to connect to two different ISPs. Which Cisco IOS security feature can you configure on R1 to reduce the risk of malicious IP spoofing while allowing traffic from Host B to reach Host A through both ISPs? A. uRPF strict modeB. IP source guardC. uRPF loose modeD. port security Answer: C QUESTION 297Which statement about Embedded Packet Capture is true? A. A capture point can be associated with muitiple capture buffersB. Capture data is stored in the router's NVRAMC. Capture data is stored in the router's DRAMD. It can capture unicast traffic onlyE. The capture configuration is persistent when the router is restarted Answer: C QUESTION 298Which ISAKMP feature can protect a GDOL from a hacker using a network sniffer while a security association is A. an ISAKMP Phase 1 security associationB. an ISAKMP Phase 2 GROUPKEY-PULL exchangeC. a ISAKMP Phase 2 GROUPKEY-PUSH exchangeD. an ISAKMP Phase 2 security associationE. the Proof of Possession(POP) Answer: A QUESTION 299Refer to the exhibit. Which Qos mechanism is in use to prioritize voice traffic? A. priority queuingB. fair queuingC. CBWFQD. low-latency queuingE. custom queuing Answer: D QUESTION 300Refer to the exhibit. Which EIGRP routes will appear in the routing table of R2? A. 2001:12::1/64B. 2001:112::/64.2001:12::1/128C. 2001:112::/64.2001:12::1/64D. 2001:12::1/128 Answer: D Lead2pass is a good website that provides all candidates with the latest IT certification exam materials. Lead2pass will provide you with the exam questions and verified answers that reflect the actual exam. The Cisco 400-101 exam dumps are developed by experienced IT professionals. 99.9% of hit rate. Guarantee you success in your 400-101 exam with our exam materials. 400-101 new questions on Google Drive: https://drive.google.com/open?id=0B3Syig5i8gpDZklpdURSVWJKalE 2017 Cisco 400-101 exam dumps (All 742 Q&As) from Lead2pass: https://www.lead2pass.com/400-101.html [100% Exam Pass Guaranteed]