

[Lead2pass New Lead2pass 2017 New 400-101 Exam PDF Ensure 400-101 Certification Exam Pass Successfully (601-620)]

Lead2pass 2017 October New Cisco 400-101 Exam Dumps! 100% Free Download! 100% Pass Guaranteed! Lead2pass presents the highest quality of 400-101 exam question which helps candidates to pass the 400-101 exams in the first attempt. Lead2pass professional tools like questions and answers are extremely reliable source of preparation. When you use Lead2pass preparation products your success in the Certification exam is guaranteed. Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/400-101.html>

QUESTION 601 Which two statements about native VLANs are true? (Choose two.) A. They require VTPv3. B. They are used to forward untagged traffic only. C. They are used to forward tagged traffic only. D. They are configured in VLAN database mode. E. They are configured under the trunk interface. F. They are used to forward both tagged and untagged traffic. Answer: BE

QUESTION 602 When you deploy DMVPN, What is the purpose of the command key cisco test address 0.0.0.0.0.0.0.0.? A. It is configured on the hub and spoke routers to establish peering. B. It is configured on the hub to set the pre-shared key for the spoke routers. C. It is configured on the internet PE routers to traverse the ISP core. D. It is configured on the spokes to router. Answer: B

QUESTION 603 Which technology allows several switches to operate together as one device? A. HSRP. B. VRRP. C. LACP. D. Stack Wise. Answer: D

QUESTION 604 Which two statements about OSPFv3 are true? (Choose two.) A. It supports the use of a cluster ID for loop prevention. B. It supports unicast address families for IPv6 only. C. It supports unicast address families for IPv4 and IPv6. D. It supports only one address family per instance. E. It supports multicast address families for IPv4. F. It supports multicast address families for IPv6. Answer: CD

QUESTION 605 Which MLD message type does a host send to join multicast groups? A. Join/prune. B. Hello. C. Query. D. Done. E. Report. F. Assert. Answer: E

QUESTION 606 Refer to the exhibit. If R1 configured as table? A. 0.0.0.0/0, 4.4.4.4/32 and 10.2.4.0/24. B. 0.0.0.0/0 and 4.4.4.4/32 only. C. 4.4.4.4/32 and 10.1.4.0/24 only. D. 4.4.4.4/32 and 10.2.4.0/24 only. E. 4.4.4.4/32, 10.2.4.0/24 and 2.2.2.2/32. Answer: D

QUESTION 607 Which TCP features allows a client to request a specific packet that was lost? A. flow control. B. sliding window. C. fast recovery. D. selective acknowledgment. Answer: D

QUESTION 608 Refer to the Exhibit. Which configuration can you implement on PE-1 to allow CE-1 to receive delegated IPv6 prefixes? A. B. C. D. E. Answer: E

QUESTION 609 What are two major requirements for configuring an extended VLAN with VTPv2 (Choose two) A. VLAN pruning must be enabled. B. The device must be operating in VTP transparent mode. C. The configuration must be made in global configuration mode. D. The VLAN must be configured in VLAN database mode. E. The reduced MAC address feature must be disabled. Answer: BC

QUESTION 610 Which two statements about MLD snooping are true? A. MLD protocol messages can be sent in both IGMPv4 and ICMPv4 formats. B. It supports private VLANs. C. It limits the Layer 2 multicast traffic that is generated by routing protocols. D. PFC modes support MLD version 2 only. E. The MLD snooping querier requires the VLAN interface to be configured with an IPv6 address. Answer: BE

QUESTION 611 Which IPv6 tunneling mechanism requires a service provider to route one of its own native IPv6 blocks to guarantee that its IPv6 hosts will be reachable? A. 6rd tunneling. B. Automatic 6to4 tunneling. C. manual ipv6ip tunneling. D. NAT-PT tunneling. E. Automatic 4to6 tunneling. F. ISATAP tunneling. Answer: A

QUESTION 612 Refer to the exhibit. After you applied this configuration to R1 and R2 they failed to form an ISIS adjacency. Which reason for the problem is most likely true? A. The network statements are mismatched. B. The IP subnets are mismatched. C. The bandwidth is mismatched. D. The MTUs are mismatched. Answer: D

QUESTION 613 Which two statements about Cisco Express Forwarding are true? (Choose two) A. Adjacency tables and Cisco Express Forwarding tables require packet switching. B. Cisco Express Forwarding tables contain forwarding information and adjacency tables contain reachability information. C. Adjacency tables and Cisco Express forwarding tables can be separately. D. Changing MAC header rewrite strings requires cache validation. E. Cisco Express Forwarding tables contain reachability information and adjacency tables contain forwarding information. Answer: CE

QUESTION 614 On which three options can Cisco PfR base its traffic routing? (Choose three) A. Time of day. B. Network performance. C. Router IOS version. D. User-defined link capacity thresholds. E. An access list with permit or deny statements. F. Load-balancing requirements. Answer: BDF

QUESTION 615 Which three statements about BGP soft reconfiguration are true? (Choose three) A. Outbound soft reconfiguration requires additional configuration on the BGP neighbor. B. Inbound soft reconfiguration requires additional memory. C. Outbound soft reconfiguration requires additional memory. D. Inbound soft reconfiguration stores an additional copy of the received from a neighbor before routing policies take effect. E. Inbound soft reconfiguration requires additional memory. F. Outbound soft reconfiguration stores an additional copy of the routes advertised to a neighbor before routing policies take effect. Answer: BEF

QUESTION 616 What mechanism should you choose to prevent unicast flooding? A. Make sure that all end systems are connected to the network with a single physical connection. B. Use control plane policing (CPP) to limit unicast flooding. C. Configure the

ARP cache timers to be longer than the switch forwarding cache (CAM) timers.D. Configure the switch forwarding cache (CAM) timers to be longer than the ARP cache timers. Answer: D QUESTION 617Refer to the exhibit. Which two statements about the device configuration are true? (Choose two.) A. The device has control-plane protection enabled.B. The device implicitly allows Tel net connections.C. The GigabitEthernet0/1 interface of the device allows incoming SSH and SNMP connections.D. The device has management-plane protection enabled.E. The device allows SSH connections to its loopback interface. Answer: CD QUESTION 618What are the two requirements for BGP to install a classful network into the BGP routing table? (Choose two.) A. Synchronization is disabled.B. The AS contains the entire classful network.C. Auto-summary is enabled.D. A classful network is statement with a classful mask is in the routing table.E. A classful network statement with a lower administrative distance ~he routing table.F. Synchronization is enabled. Answer: CD QUESTION 619Which authentication types does OSPF support? A. Null (or no authentication), clear text and MD5.B. Clear text onlyC. MD5onlyD. MD5 and clear textE. Null(or no authentication) and clear text Answer: A QUESTION 620Which metric vectors are stored but are not used by default in EIGRP? A. Reliability and delayB. Load and reliabilityC. Load and bandwidthD. Bandwidth and del Answer: B More free Lead2pass 400-101 exam new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDZ0lrZUFjNWtFYlk> Lead2pass is now here to help you with your 400-101 exam certification problems. Because we are the best 400-101 exam questions training material providing vendor, all of our candidates get through 400-101 exam without any problem. 2017 Cisco 400-101 (All 969 Q&As) exam dumps (PDF&VCE) from Lead2pass: <https://www.lead2pass.com/400-101.html> [100% Exam Pass Guaranteed]